



Medigenic Compliance Keyboards for Infection-Control

Strong arguments for improved infection-control methodology are evident where computer keyboards collect biological contaminants and require attention to maintain disinfection. The Medigenic® Compliance infection-control keyboard:

- 1) Uniquely helps monitor its own cleaning status to safeguard both patient and staff;
- 2) Features a flat design to enable quick wipe downs with hospital-grade disinfectants;
- 3) Provides standard conventional keyboard tactile feedback for high-speed data entry capability.

Features	Benefits
Flat keyboard design	 Easy to clean with readily available hospital-grade antibacterial wipes and sprays. Increases patient and staff safety. Reduces keyboard cross-contamination. No covers to constantly dispose of and replace. Ideal choice for OR and IC applications.
No raised surfaces	 Keyboard can be thoroughly cleaned with out immersion, in place, in seconds. No nooks and crannies between keys for bacteria to hide.
Sealed to IP65 standard	Can be rinsed under a faucet as necessary.Impervious to liquid cleaning products.
Time-based cleaning alert indicator. User-adjustable via PC utility software.	 Flashing light and audio alert reminds user to clean keyboard at regularly timed intervals. Cleaning the keyboard turns off indicator. Promotes good hospital hygiene practices. Preferred by clinicians to help monitor quality of care. Alert may be customized via downloadable software.
Backlit keys	• Useful in low light or dark work areas.
Excellent tactile key response with medium key travel	Capable of high-speed data entry.No cover to interfere with typing.
Clean in place	 Disinfection without disconnection. Maintain computer connectivity. No need to take keyboard off-site for cleaning.
Surface is comprised of pliant silicon- based material	Hypoallergenic and latex-free.
Configurable for multiple keyboard angle positioning	Reduces the potential for wrist strain and provides for user comfort.
Single keystroke disables keyboard during cleaning	Eliminates unwanted key entry and lengthy shutdown.
· Abrasion resistant keyboard legend overcoat	Long legend life despite cleaning and heavy usage.
User removable and replaceable cover	Extends overall product life and investment.
Unique 3-D legend graphics	Facilitates ideal visual finger placement and suggests 3-dimensional keys.
Multiple keyboard layouts available	• 104-key US or 105-key UK/Europe and 101-key US or 102-key UK/Europe versions are standard.
Keyboard interfaces – USB adaptor with auto-sense control electronics for interface protocols	• Simple connection for plug and play.

• Universal appeal.

Compatible with Microsoft Windows® 7,

Vista, XP, and 2000 operating systems

Compliance Keyboard Highlights

- Sanitize in Seconds
 Flat keyboard design quickly
 wipes clean with hospital-grade
 disinfectants. Moisture-resistant
 surface is comprised of a pliant
 silicone-based material making
 it impervious to spray or liquid
 cleaning products.
- Medigenic Alert System Indicator will flash and alert will sound at user defined intervals to promote good infection-control practices in any medical environment. Cleaning the keyboard turns off indicator.
- High-Speed Data Entry Capability Immediate tactile feedback enables users to touch-type with excellent tactile key response to quickly document care.
- Backlit Keys
 Keyboard is usable in low-light
 environments to accommodate
 data-input accuracy and reduce
 patient disturbance.
- Disinfection without disconnection.
 Single disable key to eliminate disconnection while cleaning.



Dimensions: 15.2 x 6.5 x .8 inches



Dimensions: 18.2 x 6.7 x 1.4 inches



Approved for public release

Specifications

" (387 mm) (165 mm) (19.5 mm) is (0.86 kg) ht blue ft. (2 m) r low current	18.2" (462 mm) 6.7" (170 mm) 1.4" (34 mm) 2.5 lbs (1.2 kg) light blue 6 ft. (2 m) high current po
(19.5 mm) os (0.86 kg) ht blue ft. (2 m)	1.4" (34 mm) 2.5 lbs (1.2 kg) light blue 6 ft. (2 m) high current po
s (0.86 kg) ht blue ft. (2 m) r low current	2.5 lbs (1.2 kg) light blue 6 ft. (2 m) high current po
ht blue ft. (2 m) r low current	light blue 6 ft. (2 m) high current po
ft. (2 m) r low current	6 ft. (2 m) high current po
r low current	high current po
	ŭ ,
	ŭ ,
1/102 key	104/105 key
1/102 key	104/105 key
umidity (non-co	ondensina)
<i>y</i> .	3.
ty	
	umidity (non-co

Two Year Limited Warranty assures repair or replacement. Please see warranty for complete details.



