



Infection Control Begins at the Entry Level

Medigenic Essential: Infection-Control Keyboard

Strong arguments for improved infection-control methodology are evident where computer keyboards collect biological contaminants and require attention to maintain disinfection. The Medigenic® Essential keyboard: 1) Is cost-effective for use in any medical environment; 2) Features a flat design to enable quick wipe downs with hospital-grade disinfectants; 3) Provides standard conventional keyboard tactile feedback for high-speed data entry capability.

Features	Benefits
Flat keyboard design	 Easy to clean with readily available hospital-grade antibacterial wipes and sprays. Increases patient and staff safety. Reduces keyboard cross-contamination. No covers to constantly dispose of and replace.
No raised surfaces	 Keyboard can be thoroughly cleaned without immersion, in place, in seconds. No nooks and crannies between keys for bacteria to hide.
Sealed to IP65 standard	 Can be rinsed under a faucet as necessary. Impervious to liquid cleaning products.
Excellent tactile key response with medium key travel	Capable of high-speed data entry.No cover to interfere with typing.
Clean in place	 Disinfection without disconnection. Maintain computer connectivity. No need to take keyboard off-site for cleaning.
 Surface is comprised of pliant silicon- based material 	Hypo allergenic and latex-free.
Configurable for multiple keyboard angle positioning	 Reduces the potential for wrist strain and provides for user comfort.
Single keystroke disables keyboard during cleaning	Eliminates unwanted key entry and lengthy shutdown.
Abrasion resistant keyboard legend overcoat	 Long legend life despite cleaning and heavy usage.
User removable and replaceable cover	Extends overall product life and investment.
Unique 3-D legend graphics	Facilitates ideal visual finger place- ment and suggests 3-dimensional keys.
Keyboard interfaces – USB adaptor with auto-sense control electronics for interface protocols	Simple connection for plug and play.
Compatible with Microsoft Windows® 7, Vista, XP, and 2000 operating systems	Universal appeal.

Essential Keyboard Highlights

- Cost-Effective
 Now there is a cost-effective
 alternative to conventional
 keyboards and keyboard covers.
 Ideal wherever multiple users and
 a risk of bacterial cross contamination exists.
- Sanitize in Seconds
 Flat keyboard design quickly
 wipes clean with hospital-grade
 disinfectants. Moisture-resistant
 surface is comprised of a pliant
 silicone-based material making
 it impervious to spray or liquid
 cleaning products.
- Disinfection without
 Disconnection

 Single disable key to eliminate disconnection while cleaning.
- High-Speed Data Entry Capability Immediate tactile feedback enables users to touch-type with excellent tactile key response to quickly document care.
- Hypo Allergenic Silicone-based material with no potentially irritating substances. Latex-free.
- Dimensions: 18.2 x 6.7 x 1.4 inches



Patented



ecifications

MEDIGENIC ESSENTIAL KEYBOARD

SIZE / WEIGHT / COLOR

Keyboard Length: 18.2" (462 mm) Keyboard Width: 6.7" (170 mm)

Keyboard Depth/Height (at rear minimum): 1.4" (34 mm)

Keyboard Weight: 2.5 lbs (1.2 kg) Keyboard Color: light blue Cable Length: 6 ft. (2 m)

INTERFACES

USB

KEYBOARD OPERATING SYSTEMS

Microsoft Windows® 7, Vista, XP, 2000

HOST SYSTEM REQUIREMENTS FOR A MICROSOFT WINDOWS-BASED PC

Microsoft Windows® 7, Vista, XP, 2000

USB port

MECHANICAL

QWERTY Key Life: 10,000,000 actuations per key Function Key Life: 5,000,000 actuations per key

ENVIRONMENTAL

Storage Temperature & Humidity -40° F (-40° C) to 140° F (60° C) at 5% to 65% relative humidity (non-condensing) Operating Temperature & Humidity 32° F (0° C) to 104° F (40° C) at 5% to 80% relative humidity (non-condensing)

Environmental Sealing Compliance: IP65

AGENCY AND REGULATORY APPROVALS

FCC Declaration of Conformance CFR 47 Part 15 Unintentional Radiators Class B

US and cUL Notice of Approval UL\IEC 60950

CB Scheme Certification (International) EN55024 Emissions Class B and EN55024 Immunity

CE Declaration of Conformance, Safety and EMC (European Union) EN60950

Two Year Limited Warranty assures repair or replacement. Please see warranty for complete details.



