

CHERRY SMARTTERMINAL ST-1144

USB Smart Card Reader



Models may vary from the image shown

Smart, stable and can be operated with one hand. The SmartTerminal ST-1144 reads and writes your chipcards - and with extremely low power consumption to boot. Whether access controls, network logon or smart card-based Internet transactions - the SmartTerminal with USB connection supports you in protecting your sensitive data in an easy and reliable way.

FUNCTION AND PERFORMANCE

- High-quality USB-smartcard reader
- OmniKey 3121 (Aviator) compatible
- USB 2.0-compatible
- Weighted base for "single-handed operation"

- PC/SC smartcard reader
- Protocols: T=0, T=1, S=8, S=9, S=10
- CCID compatible
- EMVco Level 1 compliant
- CAC and FIPS 201 compliant
- TAA compliant

TECHNICAL DATA

Weight main product:	300 g
Dimensions product without packaging:	51 mm x 55 mm x 75 mm
Cable-length:	175 cm
Storage temperature:	-20 °C - 50 °C
Working temperature:	0 °C - 60 °C
Product approvals:	<ul style="list-style-type: none">• cURus• GS• VCCI• CE• FCC• UKCA
System Requirements-Hardware:	USB-A
Scope of delivery:	<ul style="list-style-type: none">• Manual• Smartcard Terminal
Reliability:	MTBF > 45.000 hours
Software support:	<ul style="list-style-type: none">• Card Reader Tools• PC/SC Diagnose Tool
Model number:	ST-1144
Warranty:	3 years warranty

Errors, technical changes and delivery options reserved. Technical information refers only to the specification of the products. Properties are not guaranteed.

EAN & Part number	Color
4025112086892 ST-1144UB	black-grey