TKS-088c-TB38-MODUL



MEMBRANE HMI INDUDUR® A GETT brand

FEATURES

- Panel mount version with reserve side threaded bolts
- Excellent tactile feedback
- Haptic printing
- Integrated 38-mm trackball
- Chemical, abrasion and scratch resistant frontsheet
- Resistant against dirt, dust and liquids (IP65)

TECHNICAL DATA

Number of keys:	88
Mounting type:	front panel with threaded bolts
Front panel material:	aluminium
Keyswitch technology:	short travel keys
Switching cycles:	approx. 3 mill. (per key)
Operating force:	2.6 N
Switch travel:	0.3 mm
Protection level:	IP65 static, IP54 dynamic
Interfaces:	USB
USB compatibility:	USB V1.1 compliance
Operating temperature:	0 °C to +70 °C
Storage temperature:	-25 °C to +80 °C
Dimensions:	370 x 180 x 56 mm
Compliance:	
-- Global:	REACH, RohS self-declaration
Weight:	1100 g

TECHNICAL DATA TRACKBALL

Ball diameter:	38 mm
Ball material:	phenolic resin
Operating principle:	mechanical

Cat.No.	Product description	Interface	Layout
KS18292	TKS-088c-TB38-MODUL-USB-DE	USB	German
KS18293	TKS-088c-TB38-MODUL-USB-US	USB	US

Other language versions / interfaces / configurations available on request.

TECHNICAL DRAWING (in mm)

